



Strozzascotte

	MATERIALE	Ø SCOTTA (min / max)	INTERASSE FORI	Ø FORI
	MATERIAL	LINE SIZE (min / max)	HOLE SPACING	HOLES DIAMETER
26.02	Nylon	mm 3 / 6	mm 52	mm 4
	Nylon	1/8" - 1/4"	21/16"	5/32"
26.20	Inox	mm 3 / 6	mm 46	mm 4
	Inox	1/8" - 1/4"	113/16"	5/32"
CLAMCLEAT®				
26.03	Nylon	mm 3 / 6	mm 66	mm 4
	Nylon	1/8" - 1/4"	29/16"	5/32"
26.04	Nylon	mm 6 / 12	mm 72	mm 6
	Nylon	1/4" - 7/16"	27/8"	1/4"
26.05	Lega leggera	mm 3 / 6	mm 36	mm 4
	Aluminium	1/8" - 1/4"	17/16"	5/32"
26.06	Lega leggera	mm 6 / 12	mm 72	mm 6
	Aluminium	1/4" - 7/16"	27/8"	1/4"
26.07	Lega leggera	mm 3 / 6	mm 66	mm 5
	Aluminium	1/8" - 1/4"	29/16"	3/16"
26.08	Lega leggera	mm 3 / 6	mm 66	mm 5
	Aluminium	1/8" - 1/4"	29/16"	3/16"
26.09	Lega leggera	mm 3 / 6	mm 27	mm 4
	Aluminium	1/8" - 1/4"	11/16"	5/32"
26.10	Lega leggera	mm 4 / 8	mm 70	
	Aluminium	5/32" - 5/16"	23/4"	
26.11	Lega leggera	mm 3 / 6		
	Aluminium	1/8" - 1/4"		
26.15	Nylon	mm 2 / 4	mm 24	mm 3,5
	Nylon	5/64" - 5/32"	15/16"	9/64"

Cam cleats

26.03



26.04



New!

26.15



26.10

26.02



26.06



26.05



26.07



26.08



26.09



26.11



26.20



New!

