


DIN 7337

**Заклепка тяговая
с полукруглой шляпкой**
Нержавеющая сталь А2 (AISI 304)

| d1 | Толщина материала | Вес 100 шт./кг | d2 | l |  |
|-----|-------------------|----------------|-----|------|---|
| 3,0 | 1,0 - 3,0 | 0,158 | 6,5 | 6,0 | 500 |
| 3,0 | 3,0 - 5,0 | 0,163 | 6,5 | 8,0 | 500 |
| 3,0 | 5,0 - 7,0 | 0,159 | 6,5 | 10,0 | 500 |
| 3,0 | 7,0 - 9,0 | 0,160 | 6,5 | 12,0 | 500 |
| 3,0 | 8,0 - 2,0 | 0,175 | 6,5 | 16,0 | 500 |
| 3,2 | 1,0 - 3,0 | 0,131 | 6,5 | 6,0 | 500 |
| 3,2 | 3,0 - 5,0 | 0,136 | 6,5 | 8,0 | 500 |
| 3,2 | 5,0 - 7,0 | 0,169 | 6,5 | 10,0 | 500 |
| 3,2 | 7,0 - 9,0 | 0,175 | 6,5 | 12,0 | 500 |
| 3,2 | 9,0 - 12,0 | 0,190 | 6,5 | 16,0 | 500 |
| 4,0 | 1,0 - 2,5 | 0,216 | 8,0 | 6,0 | 500 |
| 4,0 | 2,5 - 4,5 | 0,233 | 8,0 | 8,0 | 500 |
| 4,0 | 4,5 - 6,5 | 0,244 | 8,0 | 10,0 | 500 |
| 4,0 | 6,5 - 8,5 | 0,294 | 8,0 | 12,0 | 500 |
| 4,0 | 8,5 - 12,0 | 0,309 | 8,0 | 16,0 | 500 |
| 4,0 | 11,5 - 14,0 | 0,337 | 8,0 | 18,0 | 500 |
| 4,0 | 12,0 - 16,0 | 0,364 | 8,0 | 20,0 | 500 |
| 4,8 | 2,0 - 4,0 | 0,342 | 9,5 | 8,0 | 500 |
| 4,8 | 4,0 - 6,0 | 0,485 | 9,5 | 10,0 | 500 |
| 4,8 | 6,0 - 8,0 | 0,399 | 9,5 | 12,0 | 500 |
| 4,8 | 8,0 - 11,0 | 0,450 | 9,5 | 16,0 | 500 |
| 4,8 | 10,0 - 13,0 | 0,490 | 9,5 | 18,0 | 500 |
| 4,8 | 11,0 - 15,0 | 0,529 | 9,5 | 20,0 | 500 |
| 5,0 | 2,0 - 4,0 | 0,388 | 9,5 | 8,0 | 500 |
| 5,0 | 4,0 - 6,0 | 0,389 | 9,5 | 10,0 | 500 |
| 5,0 | 6,0 - 8,0 | 0,408 | 9,5 | 12,0 | 500 |
| 5,0 | 8,0 - 11,0 | 0,491 | 9,5 | 16,0 | 500 |
| 5,0 | 10,0 - 13,0 | 0,528 | 9,5 | 18,0 | 500 |
| 5,0 | 11,0 - 15,0 | 0,566 | 9,5 | 20,0 | 500 |
| 5,0 | 15,0 - 20,0 | 0,666 | 9,5 | 25,0 | 500 |